



BN150 (BNWAS)



BRIDGE NAVIGATION WATCH ALARM SYSTEM

Designed with fleet owner / operators in mind, the BN150 from AMI is the ideal BNWAS for retrofitting to any size of vessel.

Every aspect of the system has been designed to minimise costs and inconvenience to the ship owner. From the use of simple 2 wire connection cable to the functional design of the main distribution unit, the BN150 is designed for easy and trouble free installation by the ship's crew. Setup and commissioning is very simple using the comprehensive installation manual that is supplied with every system.

An integrated 'Duty Officer Selection' function allows any combination of 5 cabins to receive 2nd stage alert. The DC-150 Display Console displays the current BNWAS status including on/off status, countdown timer, alarm status, selected cabins, active reset devices and system faults.

Reset buttons and alarms can be mounted internally or externally on bridge wings, and the volume of the alarms can be adjusted for use in different areas such as passageways or ship's office. Where approved by Class motion sensors may be used on the bridge for more convenient resetting of the timer.

Designed and manufactured in the UK, BN150 BNWAS is fully Type Approved to IEC 62616, incorporating MSC128.75.

The system is covered by a two year warranty as standard and all AMI products are supported by AMI's global network of trained service agents in over 100 locations worldwide.



**World Leaders
in Marine Interfacing
and Retransmission
Solutions**

AMI Marine (UK) Ltd
Unit 2 Tower Industrial Estate,
Tower Lane, Eastleigh, Southampton,
Hampshire, UK SO50 6NZ
Tel: +44 (0) 2380 480450
sales@amimarine.net
service@amimarine.net

www.amimarine.net





BN150 (BNWAS)



SPECIFICATIONS

Description:

DISPLAY CONSOLE (DC-150)

Main Control Panel with Backlit LCD, 3 button control and Key Switch for Set Up and Run Mode selection. Audio Visual Alarm with Reset and Emergency Call buttons.

Power:

24v DC

Dimensions:

ABS Moulded plastic 150 x 80 x 45mm IP52

Description:

DISTRIBUTION UNIT (DU-150)

Distribution Unit. Ships with DC-150 and 3m interconnect cable.

Power:

24v DC

Dimensions:

245 x 180 x 90mm IP66

Description

RESET INTERNAL (RI-150)

Illuminated Reset Button with Visual Alarm

Power:

12v DC

Dimensions:

94 x 94 x 81mm IP66

Description:

RESET EXTERNAL (RE-150)

Illuminated Reset Button with Audio Visual alarm

Power:

12v DC

Dimensions:

94 x 130 x 81mm IP66

Description:

MOTION DETECTOR (MD-150)

PIR Motion Detector (max 2 per system)

Power:

12v DC at 18mA

Dimensions:

65 x 117 x 47mm

Description:

SOUNDER BEACON (SB-150)

Alarm Sounder with Beacon. Adjustable Tone and Volume (85-102dB)

Power:

24v DC

Dimensions:

93 x 93 x 121mm IP65

Description:

SOUNDER (SD-150)

Alarm Sounder. Adjustable Tone and Volume (85-102dB)

Power:

24v DC

Dimensions:

93 x 93 x 93mm IP65

**World Leaders
in Marine Interfacing
and Retransmission
Solutions**

AMI Marine (UK) Ltd
Unit 2 Tower Industrial Estate,
Tower Lane, Eastleigh, Southampton,
Hampshire, UK SO50 6NZ
Tel: +44 (0) 2380 480450
sales@amimarine.net
service@amimarine.net

www.amimarine.net

